

Your Transmission Solution Made in the USA Since 1945



1000/1050 Series Right Angle and T-Drive Gearboxes

Driving Choice. Delivering Dependability.

All Peerless products are supported by a global dealer/distributor network of 12,000+ locations providing convenient worldwide service.

PEERLESS GEAR 1555 S. Jackson St. Salem, IN 47167 USA / US Customer Support 8 US Engineering 8 US Sales 8

812-675-GEAR (4327) 812-883-7960 812-883-7979 International Sales & Engineering 0044 7889 668531

peerlessgear.com



1000/1050 Series

Right Angle and T-Drive Gearboxes



Features & Benefits

PEERLESS 1000/1050 Series Right Angle and T-Drives are ideal for mower deck drives requiring the mower's blade to be mounted directly to the gearbox output shaft. Peerless 1050 Cast Iron Gearboxes are available for heavy-duty and high impact applications.

- Housing 1000 Series Die Cast Aluminum 1050 Series – Cast Iron
- Shafts 7/8" (22.2 mm) diameter Customer specific shaft designs available
- Bearings All shafts mounted on ball bearings
- Gears Heavy duty and heat treated cut steel
- Output Rotation CW in = CW out CW in = CCW out
- Lubrication EP-90 gear oil
- Couplings Available to couple units together for deck drive
- Connector Shafts Available to couple units together for deck drive
- Gear Ratios 1.2:1, 1:1, and .833:1
- Applications Mower cutter box drive, angle power transfer, heavy duty steering box, and concrete saws

Note: Specifications subject to change without notice.

PEERLESS GEAR 1555 S. Jackson St. Salem, IN 47167 USA US Customer Support 812-675 US Engineering 812-883 US Sales 812-883

812-675-GEAR (4327) 812-883-7960 812-883-7979 International Sales & Engineering 0044 7889 668531

peerlessgear.com

Through Gearbox 1000 Series Aluminum Housing 10 HP 1050 Series Cast Iron Housing 13 HP

Your Transmission Solution Made in the USA Since 1945

Technical Specs

Maximum Input Speed 3,600 RPM

Recommended HP

Maximum Static Torque 100 ft. lbs. (135.6 N-m)

Weight on Tires

1000 Series 6 lbs (2.7 kg) 1050 Series 9 lbs (4.1 kg)

Options

Couplings with internal splines, connector shafts, various shaft ends and types, and customer requested shafts